

Unigloves

Product specification sheet

Revision 4 | 17 October 2017

1.	Product code	GS022*																											
2.	Product description	Unicare Flex Blue Nitrile powder free 200s																											
3.	Material	Nitrile																											
4.	Inspection parameters	<table><tr><th>Criteria</th><th>Inspection level</th><th>AQL</th><th>Standard</th></tr><tr><td>Dimensions</td><td>S-2</td><td>4</td><td>EN455-2</td></tr><tr><td>Physical properties</td><td>S-2</td><td>4</td><td>EN455-2</td></tr><tr><td>Water tight test (1,000ml)</td><td>G-1</td><td>4</td><td>EN455-1</td></tr><tr><td>Visual defects</td><td>G-1</td><td>2.5</td><td>In-house</td></tr></table>				Criteria	Inspection level	AQL	Standard	Dimensions	S-2	4	EN455-2	Physical properties	S-2	4	EN455-2	Water tight test (1,000ml)	G-1	4	EN455-1	Visual defects	G-1	2.5	In-house				
Criteria	Inspection level	AQL	Standard																										
Dimensions	S-2	4	EN455-2																										
Physical properties	S-2	4	EN455-2																										
Water tight test (1,000ml)	G-1	4	EN455-1																										
Visual defects	G-1	2.5	In-house																										
5.	Glove dimensions	<table><tr><th rowspan="2">Dimensions</th><th colspan="4">Size (mm)</th></tr><tr><th>S</th><th>M</th><th>L</th><th>XL</th></tr><tr><td>Product code</td><td>GS0222</td><td>GS0223</td><td>GS0224</td><td>GS0225</td></tr><tr><td>Palm width</td><td>80 ± 10</td><td>95 ± 10</td><td>110 ± 10</td><td>≥ 110</td></tr><tr><td>Length</td><td>≥ 240</td><td>≥ 240</td><td>≥ 240</td><td>≥ 240</td></tr></table>				Dimensions	Size (mm)				S	M	L	XL	Product code	GS0222	GS0223	GS0224	GS0225	Palm width	80 ± 10	95 ± 10	110 ± 10	≥ 110	Length	≥ 240	≥ 240	≥ 240	≥ 240
Dimensions	Size (mm)																												
	S	M	L	XL																									
Product code	GS0222	GS0223	GS0224	GS0225																									
Palm width	80 ± 10	95 ± 10	110 ± 10	≥ 110																									
Length	≥ 240	≥ 240	≥ 240	≥ 240																									
6.	Glove thickness	<table><tr><th>Point of thickness measurement</th><th>Nominal single wall (mm)</th></tr><tr><td>Cuff (at beaded end)</td><td>0.04</td></tr><tr><td>Palm (at centre of palm)</td><td>0.05</td></tr><tr><td>Fingertip (at fingertip)</td><td>0.06</td></tr></table>				Point of thickness measurement	Nominal single wall (mm)	Cuff (at beaded end)	0.04	Palm (at centre of palm)	0.05	Fingertip (at fingertip)	0.06																
Point of thickness measurement	Nominal single wall (mm)																												
Cuff (at beaded end)	0.04																												
Palm (at centre of palm)	0.05																												
Fingertip (at fingertip)	0.06																												
7.	Physical properties	<table><tr><th>Parameters</th><th>Before aging</th><th>After aging</th></tr><tr><td>Median force at break (N)</td><td>N/A</td><td>N/A</td></tr><tr><td>Tensile strength (MPa)</td><td>Min 14.0</td><td>Min 14.0</td></tr><tr><td>Ultimate elongation (%)</td><td>Min 500</td><td>Min 400</td></tr></table>				Parameters	Before aging	After aging	Median force at break (N)	N/A	N/A	Tensile strength (MPa)	Min 14.0	Min 14.0	Ultimate elongation (%)	Min 500	Min 400												
Parameters	Before aging	After aging																											
Median force at break (N)	N/A	N/A																											
Tensile strength (MPa)	Min 14.0	Min 14.0																											
Ultimate elongation (%)	Min 500	Min 400																											
8.	Proteins	None																											
9.	Powder residue	Maximum 2.0 mg / glove																											
10.	Cuff type	Beaded																											
11.	Design	Ambidextrous																											
12.	Surface	Fingertip textured																											
13.	Colour	Blue																											
14.	Quality assurance	Manufactured under ISO 9001 and 13485																											
15.	Weight (based on size medium)	2.2g																											

The above data represents the product norm, which may be changed without notice and is intended as a guide only.