

PIG® Above-the-Ceiling Leak Diverter

TLS620 56cm x 82cm x 18cm

This light-weight leak diverter sits directly on your ceiling tile to channel liquid away and help prevent damage.

- Installed diverter remains completely out of view whilst diverting ceiling leaks
- Mounted on a light-weight, sturdy frame that sits on suspended 61cm x 61cm or 61cm x 122cm acoustical tile
- Nonpermeable tarp is vinyl-coated for strength and durability; resists punctures, UV and mildew for long life
- Captured liquid drains through a 1/4" port into the attached 762cm long PVC hose
- Assembles in less than 5 minutes, then it's ready to install above your drop ceiling
- Install side by side to protect larger areas



Item#	Description	Dimensions	Weight
TLS620-CL	Clear	56cm W x 82cm L x 18cm H	2.4 kg

Metric Equivalent:

Item#	Description	Dimensions	Weight
TLS620-CL	Clear		

Specifications

Use With	Drop Ceilings
Dimensions	56cm W x 82cm L x 18cm H
Drainage Hose Included	Yes
Grommets/D-Rings	N/A
Hanging Straps Included	No
Hose Connector	.25"
Installation Method	Frame
Sold as	1 each
Weight	2.4 kg
New Pig Patent	7,331,357
# per Pallet	40

Composition	Diverter - PVC w/ Polyester Reinforcement; Frame, Hose -
-------------	--

	PVC
Flow Rate	4 ltr. per Minute
Includes	1 - 76cm x 107cm Vinyl Sheet 1 - PVC Frame 1 - 762cm L Hose
Thickness	300 micron

Disclaimers

Maximum Working Temperature

Not suitable for temperatures over 170°F/77°C.

Assembly Required



Hogs Hill • Watt Place • Hamilton International Technology Park • Blantyre • Glasgow • G72 0AH
0800 919 900 • newpig.co.uk • pigpen@newpig.com